

RX MONO



Car HiFi

Magnat®

Magnat Audio-Produkte GmbH • Lise-Meitner-Str. 9 • 50259 Pulheim • Tel: 02234/807-0 • Fax 02234/807-399
www.magnat.de • Info@Magnat.de

RX MONO

2



Car HiFi

Magnat®

RX MONO

3



Besonderheiten

- Stabil an 1 Ohm
- Variabler Tiefpass 40 – 250 Hz (12 dB/Oktave)
- Variabler Subsonicfilter 10 – 40 Hz (12 dB/Oktave)
- Variabler Bass Boost 0...12dB bei 45 Hz
- Niederpegelausgänge
- Gekapselte Strom- und Lautsprecherklemmen
- Schutzschaltung gegen Kurzschluss, Gleichspannungs-Offset und Übertemperatur
- Betriebsanzeige (grüne LED) und Überlastanzeige (rote LED)
- Fernbedienung für die Lautstärkeregelung

Highlights

- 1 ohm stable
- Variable low pass 40 – 250 Hz (12 dB per octave)
- Variable bass boost 0...12 dB at 45 Hz
- Variable subsonic filter 10 – 40 Hz (12 dB per octave)
- Low level RCA outputs
- Encapsulated power and speaker connectors
- Protection circuit that safeguards against short circuits, DC-offset and overheating
- Green operation and red protection indication LED
- Remote volume control

Car HiFi

Magnat[®]

RX MONO



Art.-Nr: **132 20661**
EAN: **40 18843 2066 15**

Technische Daten

• Max. Ausgangsleistung (Sinus Burst 2:8, 1 kHz) an 4 Ohm, 14,4 V	1000 Watt
• Nennleistung (DIN 45 324) an 4 Ohm, 14,4 V	350 Watt
• Max. Ausgangsleistung (Sinus Burst 2:8, 1 kHz) an 2 Ohm, 14,4 V	1400 Watt
• Nennleistung (DIN 45 324) an 2 Ohm, 14,4 V	500 Watt
• Max. Ausgangsleistung (Sinus Burst 2:8, 1 kHz) an 1 Ohm, 14,4 V	2000 Watt
• Nennleistung (DIN 45 324) an 1 Ohm, 14,4 V	800 Watt
• Frequenzgang	5 Hz - 250 Hz (-3 dB)
• Klirrfaktor	< 0,05 % (1 kHz)
• Geräuschspannungsabstand (A-Filter)	> 100 dB
• Eingangsempfindlichkeit	0,2 V - 6 V
• Eingangsimpedanz	20 kOhm
• Stromversorgung	12 V minus an Masse
• Abmessungen (BxHxT)	450 mm x 50 mm x 261 mm
• Gewicht	4,85 kg

specifications

• Max. power output (sine burst 2:8, 1 KHz) @ 4 ohms, 14.4 V	1000 watts
• RMS power output (DIN 45 324) @ 4 ohms, 14.4 V	350 watts
• Max. power output (sine burst 2:8, 1 kHz) @ 2 ohms, 14.4 V	1400 watts
• RMS power output (DIN 45 324) @ 2 ohms, 14.4 V	500 watts
• Max. power output (sine burst 2:8, 1 kHz) @ 1 ohms, 14.4 V	2000 watts
• RMS power output (DIN 45 324) @ 1 ohms, 14.4 V	800 watts
• frequency response	5 Hz - 250 Hz (-3 dB)
• THD	< 0,05 % (1kHz)
• Signal-to-noise ratio (A-weighted)	> 100 dB
• Input sensitivity	0,2 V - 6 V
• Input impedance	20 kOhms
• Power Supply	12 V negative ground
• Dimensions (WxHxD)	450 mm x 50 mm x 261 mm
• Weight	4,85 kg

Car HiFi

Magnat®