



Competition Subwoofer

Thiele-Small Parameter


	RS C 8 SVC	RS C 10 SVC	RS C 12 SVC
Fs	42,45	30,09	29,27
Mmd	88,81	115,4	163,82
Mms	90,59	119,2	170,06
Cms	155,13	234,72	173,84
Vas	9,99	41,3	59,27
Xmax(+/-)	10,5	10,5	10,5
Sd	0,0021	0,035	0,049
Re	3,8	3,7	3,8
Le	3,075	3,344	3,52
Bl	12,48	15,06	16,36
Spl	84,2	86,73	87,19
Qms	8,12	5,54	5,962
Qes	0,58	0,368	0,444
Qts	0,55	0,345	0,413

Gehäusevorschläge

Enclosure-volumes

RS C 8 SVC


Geschlossenes Gehäuse
Sealed Enclosure



Gehäuse Innenvolumen
Enclosure Volume inside
10,5 Liter

RS C 10 SVC


Geschlossenes Gehäuse
Sealed Enclosure



Gehäuse Innenvolumen
Enclosure Volume inside
22,5 Liter

RS C 12 SVC

Geschlossenes Gehäuse
Sealed Enclosure



Gehäuse Innenvolumen
Enclosure Volume inside
31,5 Liter

HEAR THE DIFFERENCE

www.rs-audio.de