

165 VRS

Polyglass kit

- Butyl surround
Promoting long life
- Shallow mounting (56mm / 2^{3/16"})
Easy integration in the most exiguous spaces
- Polyglass cone
Neutral sound without coloration

- Zamak basket
Strong rigid chassis, non magnetic, non resonant
- 32mm (1-1/4") voice coil on Kapton® former
High power handling
- 38 SH neodymium magnet
High magnetic field for a high sensitivity

- Air core inductor with a low serial resistance
Insensitive to parasites, better sensitivity
- Adjustable tweeter level
Tweeter level setting according to the positioning
- Polypropylene/Aluminum capacitor
Natural reproduction of high frequencies



- Dual push-pull neodymium magnet
Excellent linearity of the tweeter
- Voice coil on aluminum former
High dissipation characteristics
- Aluminum/magnesium inverted dome TNB tweeter
Smooth and detailed treble, large and precise sound stage

Technical characteristics :

165mm (6^{1/2"}) **woofer**
 32mm (1^{1/4"}) **voice coil**
 38 SH **neodymium magnet**
 45mm (1^{3/4"}) **TNB tweeter**
Aluminum/magnesium inverted dome tweeter
 12-18dB/octave **2-way crossover (4.9kHz)**
Adjustable tweeter level (0, -3, -6dB)
Max. power: 120W
Nom. power: 60W rms
Sensitivity (2.8V/1m): 93dB
Frequency response: 70Hz – 28kHz
Accessories : grilles provided

It makes the difference :

- Easy installation for all kind of vehicles (shallow mounting: 56mm / 2^{3/16"})
- Hi-Fi sound for an optimized realism
- Large and precise sound stage
- Important dynamic
- Forceful bass
- The essentially of the Focal sound

